

Trunk Mounted Flag Holder FH200

1. This flag holder is designed to be mounted on the side of a trunk or tour pack using both the adhesive pad and the threaded stud. This will require drilling a 1/4" hole thru the trunk or tour pack.
2. Find a suitable location on the side or back of the trunk or tour pack. Be sure that the location you chose does not interfere with the lid if the trunk or tour pack when opened and that the flag pole is vertical (straight) when viewed from both the rear and side of the motorcycle (you may want to have it swept back 10 to 15 degrees when viewed from the side). This can be done by having another person hold it in place while you look at it from both directions or by using some masking tape over the round base and holding it to the trunk or tour pack.
3. Place some masking tape in the general area you have chosen to mount the flag holder. Place the round base where you want it, again being sure it will be vertical (straight up and down) when viewed from the rear. Trace around the base using a pen or pencil. Look at the inside of the trunk or tour pack to see that there is room to install the stud and nut after the hole will be drilled.
4. Drill a 9/32" (just over 1/4") hole thru the trunk or tour pack at the center of the traced circle. Remove the masking tape. Thread the stud into the base. Peel the protective paper from the adhesive pad on the back of the mounting base. Place the stud thru the hole, align the pole as desired, either vertical or swept back 10 to 15 degrees when viewed from the side and press the base very lightly in place. Now one more time stand back and verify that the pole is where you like it then press the base firmly in place. Place the washer, lock washer and nut onto the stud and tighten only enough to seat the double sided tape on the base firmly against the trunk or tour pack do not over tighten as this will place undue stress on the trunk or tour pack.
5. Unscrew the flag poles top finial and slide off the two plastic clips. Place your flag onto the pole and replace the finial. Tighten the finial and poles base lock nuts securely. Snap the plastic clips over the flag on the pole; these will keep the flag in place at the top of the pole.

440 South Pine Street
Burlington, WI 53105
888-801-8222
rivcoproducts.com

